



This riser rated OM4 laser-optimized multimode (LOMMF) MPO fiber cable is ready for deployment in any multimode 50/125 MTP/MPO network. OM4 is fully backward-compatible with existing OM3 systems. This multimode, MPO fiber cable is comprised of 8 fibers or 4 duplex channels within each connector (the center 4 fibers are not used). These high density cables are perfect when you have limited space, making it possible to run a single cable that automatically terminates 8 fibers in one easy plug-in. The fan-out side has 8 LC connectors that are numbered according to the fiber position in the MPO Connector and duplexed together. The push-pull release mechanism for the MPO connector is easy to engage and disengage, its latch design also prevents the plug from snagging when jumper cables are being routed.

Features & Benefits

- Labeled duplex LC connectors correspond with the fiber pinout on the MPO connector (No guide pins)
- 3mm diameter at the MPO side to 2mm on the breakout side
- Riser rated (OFNR) Jacket
- MPO fans out to 8 Fibers with LC connectors

Specifications

General Info

| | | | |
|-------------------|-----------|--------------------|------------------------|
| Product Line | C2G | UPC Number | 757120313311 |
| Country Of Origin | Hong Kong | Application Sector | Commercial, Industrial |
| Type | Cable | | |

Dimensions

| | |
|--------------|--------|
| Cable Length | 3.3 ft |
|--------------|--------|

Additional Information

| | | | |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

Technical Information

| | | | |
|--------------|------------------------------------|-----------------|--------------------------|
| Cable Type | Multimode, OM4, MPO, MTP | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius | 45 mm | Simplex/Duplex | Full-Duplex |
| Cable Type | Fiber Optic, Breakout | Jacket Rating | Riser OFNR-Rated |
| Adapter Rear | LC Male, LC Male, LC Male, LC Male | Adapter Front | MPO Male |

