




C2G
6.6ft (2m) MTP® Compatible MPO to 4 Duplex Fiber Breakout Cable OM4 riser rated (OFNR)
Part No. CG-31332



This riser rated OM4 laser-optimized multimode (LOMMF) MPO fiber cable is ready for deployment in any multimode 50/125 MTP/MPO network. OM4 is fully backward-compatible with existing OM3 systems. This multimode, MPO fiber cable is comprised of 8 fibers or 4 duplex channels within each connector (the center 4 fibers are not used). These high density cables are perfect when you have limited space, making it possible to run a single cable that automatically terminates 8 fibers in one easy plug-in. The fan-out side has 8 LC connectors that are numbered according to the fiber position in the MPO Connector and duplexed together. The push-pull release mechanism for the MPO connector is easy to engage and disengage, its latch design also prevents the plug from snagging when jumper cables are being routed.

Features & Benefits

Labeled duplex LC connectors correspond with the fiber pinout on the MPO connector (No guide pins) Riser rated (OFNR) Jacket

3mm diameter at the MPO side to 2mm on the breakout side MPO fans out to 8 Fibers with LC connectors

Specifications

General Info

Product Line	C2G	UPC Number	757120313328
Country Of Origin	Hong Kong	Application Sector	Commercial, Industrial
Warranty Type	Lifetime	Type	Cable

Dimensions

Cable Length 6.6 ft

Additional Information

Prop 65 Warning Required Yes Prop 65 Warning Language Cancer and Reproductive Harm

Technical Information

Fiber Optic Cable Type	Multimode, OM4, MPO, MTP	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	45 mm	Simplex/Duplex	Full-Duplex
Cable Type	Fiber Optic, Breakout	Jacket Rating	Riser OFNR-Rated
Adapter Rear	LC Male, LC Male, LC Male, LC Male	Adapter Front	MPO Male

