



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve 50/125 single-mode fibers under one PVC (OFNR-rated) jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPO is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

## Features & Benefits

- Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer
- Small form factor provides a higher port density
- Ease of installation - simply pull one cable rather than twelve
- Push-pull release mechanism and latch design for easy use

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120314066	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

### Dimensions

Cable Length	16.4 ft
--------------	---------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Cable Type	Multimode, OM2, MTP	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	45 mm	Cable Type	Fiber Optic
Jacket Rating	Riser OFNR-Rated	Data Transfer Rate	10 Gbps

---

Adapter Rear

MPO Female

Adapter Front

MPO Female

---

Fiber Size

50/125

---