



Make MTP/MPD your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPD's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPD fiber assembly consists of twelve 50/125 single-mode fibers under one PVC (OFNR-rated) jacket.

With our MTP/MPD, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPD connector provides a higher port density. With its push-pull release mechanism, the MTP/MPD connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPD is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

## Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer

Ease of installation - simply pull one cable rather than twelve

Small form factor provides a higher port density

Push-pull release mechanism and latch design for easy use

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120314110	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

### Dimensions

Cable Length	164 ft
--------------	--------

### Technical Information

Fiber Optic Cable Type	MTP, Multimode, OM2	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	45 mm
Cable Type	Fiber Optic	Jacket Rating	FT4 Rated, OFNR Rated
Cable Diameter	3 mm	Data Transfer Rate	10 Gbps
Connector 2	MPD Female	Connector 1	MPD Female

---

Fiber Size	50/125
------------	--------

---