



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve 62.5/125µm single-mode fibers under one PVC (OFNR-rated) jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

**Please Note:** MTP/MPO is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

## Features & Benefits

- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications
- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications
- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications
- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications
- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications
- Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120314127	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

### Dimensions

Cable Length	16.4 ft
--------------	---------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

---

## Technical Information

---

Cable Type	Multimode, OM1, MTP	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	45 mm	Cable Type	Fiber Optic
Jacket Rating	Riser OFNR-Rated	Data Transfer Rate	1 Gbps
Adapter Rear	MPO Female	Adapter Front	MPO Female
Fiber Size	62.5/125		

---