



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve laser-optimized, 10G 50/125 multimode fibers under one PVC (OFNR-rated) jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPO is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

Features & Benefits

- Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer
- Small form factor provides a higher port density
- Ease of installation - simply pull one cable rather than twelve
- Push-pull release mechanism and latch design for easy use

Specifications

General Info

Product Line	C2G	Color	Aqua
UPC Number	757120314196	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

Dimensions

Cable Length	33 ft
--------------	-------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Cable Type	Multimode, OM3, MTP	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	45 mm	Cable Type	Fiber Optic
Jacket Rating	Riser OFNR-Rated	Data Transfer Rate	10 Gbps
Adapter Rear	MPO Female	Adapter Front	MPO Female
Fiber Size	50/125		
