



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

Features & Benefits

Perfect for high-bandwidth, high transmission rate applications over long distances Available in SC, ST and LC connectors
 Available in lengths up to 30m

Specifications

General Info

Product Line	C2G	Color	Orange
UPC Number	757120330288	Country Of Origin	China
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	6.6 FT	Cable Length	6.6 ft
-------------------	--------	--------------	--------

Technical Information

Fiber Optic Cable Type	Multimode, OM2	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic

Jacket Rating	FT4 Rated, OFNR Rated	Cable Diameter	1.8 mm
Data Transfer Rate	10 Gbps	Connector 2	LC Male
Connector 1	LC Male	Fiber Size	50/125
