




C2G  
**DISCONTINUED: 164ft (50m) MTP/MPO 62.5/125 Multimode Fiber Optic Assembly Ribbon Cable - Plenum CMP-Rated - Orange (TAA Compliant)**  
Part No. CG-33092



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve laser-optimized, 62.5/125 multimode fibers under one OFNP plenum-rated jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPO is a registered trademark of US Conec Ltd.

## Features & Benefits

- Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer
- Ease of installation - simply pull one cable rather than twelve
- Push-pull release mechanism and latch design for easy use
- Plenum rated for cable runs through walls and drop ceilings with plenum air space
- Small form factor provides a higher port density

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120330929	Country Of Origin	United States
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Cable Length	164 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Fiber Optic Cable Type	Multimode, MPO, MTP	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	45 mm	Cable Type	Fiber Optic
Jacket Rating	Plenum CMP-Rated	Adapter Rear	MTP
Adapter Front	MTP	Fiber Size	62.5/125