



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve 9/125 single-mode fibers under one PVC (OFNR-rated) jacket. With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density.

The LSZH jacket is composed from materials that lessen the smoke and halogen emissions when the cable is exposed to extreme temperatures.

This reduces the amount of harmful toxic and corrosive gases that cabling made with plastic materials would otherwise emit into the air during combustion. This construction makes LSZH cables ideal for use where the protection of people and equipment from harmful corrosive gases is absolutely critical.

With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

Please Note: MTP/MPO is a registered trademark of US Conec Ltd.

Features & Benefits

Designed to support gigabit ethernet, fibre channel, ATM, or any application that requires high speed data transfer

Low Smoke Zero Halogen (LSZH) jacket lessen harmful smoke and halogen emissions when the cable is exposed to extreme temperatures

Ease of installation - simply pull one cable rather than twelve

Small form factor provides a higher port density

Push-pull release mechanism and latch design for easy use

Specifications

General Info

Product Line	C2G	Color	Yellow
UPC Number	757120351047	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

Dimensions

Cable Length	98.4 ft
--------------	---------

Technical Information

Fiber Optic Cable Type	MTP, OS1, Single-Mode	Jacket Material	LSZH PVC
Jacket Application	Riser Rated	Bend Radius	45 mm
Cable Type	Fiber Optic	Jacket Rating	FT4 Rated, OFNR Rated
Cable Diameter	3 mm	Connector 2	MTP
Connector 1	MTP	Fiber Size	9/125