



This OM3 Duplex Multimode Fiber Optic Cable is ideal for connecting 10GBase-SR, 10GBase-LRM, SFP+ and QSFP+ transceivers for 10 gigabit network connections. This cable has a OFNP-rated jacket allowing it to be used in a plenum application. This cable also provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 10 gigabit ethernet applications.

Features & Benefits

- Designed to support 10 gigabit ethernet applications
- OFNP- rated for cable runs through walls and drop ceilings with plenum air space
- Backward compatibility with existing 50/125 equipment

Specifications

General Info

Product Line	C2G	Color	Aqua
UPC Number	757120362418	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

Dimensions

Cable Length	3.3 ft
--------------	--------

Technical Information

Fiber Optic Cable Type	Multimode, OM3	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Plenum Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic
Jacket Rating	CMP Rated, FT6 Rated	Cable Diameter	1.8 mm
Data Transfer Rate	10 Gbps	Connector 2	ST Male
Connector 1	LC Male	Fiber Size	50/125