



With SC to ST termination, this high quality fiber optic patch cable is specifically designed for ethernet, multimedia, or communication applications. The SC connector features a push-pull locking system while the ST connector features a bayonet locking system.

The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

Features & Benefits

| | |
|---|---|
| Designed to support ethernet, multimedia, or communication applications | Patented injection molding process for greater durability |
| Optically inspected and tested for insertion loss | Pull-proof jacket design, immune to electrical interference |

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|-----------|
| Product Line | C2G | Color | Red |
| UPC Number | 757120371557 | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type | Cable |

Dimensions

| | |
|--------------|--------|
| Cable Length | 6.6 ft |
|--------------|--------|

Technical Information

| | | | |
|------------------------|-----------------------|--------------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM1 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Riser Rated | Bend Radius | 50 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |
| Jacket Rating | FT4 Rated, OFNR Rated | Data Transfer Rate | 1 Gbps |
| Connector 2 | ST Male | Connector 1 | SC Male |
| Fiber Size | 62.5/125 | | |