

With SC to SC termination, this high quality fiber optic patch cable is specifically designed for ethernet, multimedia, or communication applications. The SC connector features a push-pull locking system.



The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

## Features & Benefits

- Designed to support ethernet, multimedia, or communication applications
- Patented injection molding process for greater durability
- Optically inspected and tested for insertion loss
- Pull-proof jacket design, immune to electrical interference

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Red       |
| UPC Number         | 757120371755           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Warranty Type     | Lifetime  |
| Type               | Cable                  |                   |           |

### Dimensions

|              |        |
|--------------|--------|
| Cable Length | 6.6 ft |
|--------------|--------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

---

|                        |                |                 |                          |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM1 | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius            | 50 mm          | Simplex/Duplex  | Duplex                   |
| Cable Type             | Fiber Optic    | Jacket Rating   | Riser OFNR-Rated         |
| Data Transfer Rate     | 1 Gbps         | Adapter Rear    | SC Male                  |
| Adapter Front          | SC Male        | Fiber Size      | 62.5/125                 |

---