



With SC to SC termination, this high quality fiber optic patch cable is specifically designed for ethernet, multimedia, or communication applications. The SC connector features a push-pull locking system. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

Features & Benefits

- Designed to support gigabit ethernet, FDDI, multimedia, ATM, or any application that requires high speed data transfer
- Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space
- Patented injection molding process for greater durability
- Optically inspected and tested for insertion loss
- Pull-proof jacket design, immune to electrical interference

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|----------|
| Product Line | C2G | Color | Orange |
| UPC Number | 757120372790 | Country Of Origin | China |
| Application Sector | Commercial, Industrial | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 32.8 FT | Cable Length | 33 ft |
|-------------------|---------|--------------|-------|

Technical Information

| | | | |
|------------------------|----------------------|--------------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM1 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Plenum Rated | Bend Radius | 50 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |
| Jacket Rating | CMP Rated, FT6 Rated | Data Transfer Rate | 1 Gbps |
| Adapter Rear | SC Male | Adapter Front | SC Male |

Fiber Size

62.5/125
