



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

## Features & Benefits

- OM2 - 50µm core
- OFNR - Riser rated jacket
- Supports 500 MHz km OFL at 850/1300nm
- Tested in accordance with EIA/TIA-455-171A

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120374008	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

### Dimensions

Cable Length	3.3 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Cable Type	Multimode, OM2	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	50 mm	Simplex/Duplex	Duplex

---

Cable Type	Fiber Optic	Jacket Rating	Riser OFNR-Rated
Data Transfer Rate	10 Gbps	Adapter Rear	ST Male
Adapter Front	LC Male	Fiber Size	50/125

---