



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference. These multicolored fiber optic patch cables enable you to quickly identify various applications present in your fiber distribution system. The connectors on each end are color-coded for easy identification in a congested patch field.

Features & Benefits

| | |
|--|---|
| Designed to support gigabit ethernet, fibre channel, Infiniband, ATM, and internet protocol applications | Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space |
| Patented injection molding process for greater durability | Optically inspected and tested for insertion loss |
| Pull-proof jacket design, immune to electrical interference | Color-coded connectors for easy identification |

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|-----------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120375814 | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type | Cable |

Dimensions

| | |
|--------------|--------|
| Cable Length | 6.6 ft |
|--------------|--------|

Technical Information

| | | | |
|------------------------|----------------------|--------------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM2 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Plenum Rated | Bend Radius | 50 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |
| Jacket Rating | CMP Rated, FT6 Rated | Data Transfer Rate | 10 Gbps |
| Connector 2 | ST Male | Connector 1 | SC Male |
| Fiber Size | 50/125 | | |