



Cost-effective solution that provides higher bandwidth and transmission rates and supports longer distances with lower loss than 62.5/125 fiber. Specifically designed for use with today's narrower aperture components, this cable is fully compatible with multimode applications. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 50/125 multimode fiber, immune to electrical interference.

Features & Benefits

OM2 - 50µm core	Supports 500 MHz km OFL at 850/1300nm
OFNP - Plenum rated jacket	Tested in accordance with EIA/TIA-455-171A

Specifications

General Info

Product Line	C2G	Color	Red
UPC Number	757120376590	Country Of Origin	China
Application Sector	Commercial, Industrial	Type	Cable

Dimensions

Product Length US	32.8 FT	Cable Length	33 ft
-------------------	---------	--------------	-------

Technical Information

Fiber Optic Cable Type	Multimode, OM2	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Plenum Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic
Jacket Rating	CMP Rated, FT6 Rated	Data Transfer Rate	10 Gbps
Connector 2	LC Male	Connector 1	LC Male
Fiber Size	50/125		