



Cost-effective solution that provides high bandwidth and transmission rates over longer distances. With SC to ST termination, this high quality fiber optic patch cable is specifically designed for gigabit ethernet applications. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 9/125 Single-mode fiber, immune to electrical interference.

## Features & Benefits

Designed to support gigabit ethernet, fibre channel, Infiniband, ATM, and internet protocol applications	Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space
Patented injection molding process for greater durability	Optically inspected and tested for insertion loss
Pull-proof jacket design, immune to electrical interference	Color-coded connectors for easy identification

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120376620	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Cable Length	9.8 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Fiber Optic Cable Type	Single-Mode, OS2	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Plenum Rated	Bend Radius	50 mm
Simplex/Duplex	Simplex	Cable Type	Fiber Optic
Jacket Rating	CMP Rated, FT6 Rated	Adapter Rear	ST Male
Adapter Front	SC Male	Fiber Size	9/125