



Cost-effective solution that provides high bandwidth and transmission rates over longer distances. With LC to ST termination, this high quality fiber optic patch cable is specifically designed for gigabit ethernet applications. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 9/125 Single-mode fiber, immune to electrical interference.

## Features & Benefits

- Designed to support gigabit ethernet applications
- Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space
- Patented injection molding process for greater durability
- Optically inspected and tested for insertion loss
- Pull-proof jacket design, immune to electrical interference

## Specifications

### General Info

|                    |                        |                   |           |
|--------------------|------------------------|-------------------|-----------|
| Product Line       | C2G                    | Color             | Blue      |
| UPC Number         | 757120376880           | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type              | Cable     |

### Dimensions

|              |         |
|--------------|---------|
| Cable Length | 16.4 ft |
|--------------|---------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

|              |                 |                 |                          |
|--------------|-----------------|-----------------|--------------------------|
| Cable Type   | Singlemode, OS2 | Jacket Material | PVC (Polyvinyl Chloride) |
| Bend Radius  | 50 mm           | Simplex/Duplex  | Simplex                  |
| Cable Type   | Fiber Optic     | Jacket Rating   | Plenum CMP-Rated         |
| Adapter Rear | ST Male         | Adapter Front   | LC Male                  |
| Fiber Size   | 9/125           |                 |                          |