



Cost-effective solution that provides high bandwidth and transmission rates over longer distances. With LC to ST termination, this high quality fiber optic patch cable is specifically designed for gigabit ethernet applications. The plenum rating provides the fire protection required to run this cable within walls and air plenums without using conduit. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 9/125 Single-mode fiber, immune to electrical interference.

Features & Benefits

- Designed to support gigabit ethernet applications
- Patented injection molding process for greater durability
- Pull-proof jacket design, immune to electrical interference
- Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space
- Optically inspected and tested for insertion loss

Specifications

General Info

Product Line	C2G	Color	Yellow
UPC Number	757120379089	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Type	Cable

Dimensions

Cable Length	16.4 ft
--------------	---------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Cable Type	Singlemode, OS2	Jacket Material	PVC (Polyvinyl Chloride)
Bend Radius	50 mm	Simplex/Duplex	Duplex
Cable Type	Fiber Optic	Jacket Rating	Plenum CMP-Rated
Adapter Rear	ST Male	Adapter Front	LC Male
Fiber Size	9/125		