

Small form factor: 1.125in x 5.125in x 4.5in. This breakout module provides the mechanical distribution of the 12-strand MTP/MPO connector. Housed in a rugged steel enclosure guaranteed for life, this durable module arrives fully loaded with the preterminated and tested MTP/MPO breakout harness. It is shipped with a test report that can assist in calculating the optical budget.



Not only does that reduce your installation time, but it also ensures optimum quality, performance and consistency. For additional flexibility, you can fit this in one of our rack or wallmount enclosures which feature scalable designs that can grow with your network system.

Please Note: Custom module configurations supporting other fiber types are also available upon request, and can be quickly fulfilled.

Note: This cassette uses Method A (straight through polarity). To ensure proper transmit to receive polarity between equipment, use one of the following methods.

- Use an MTP/MPO Trunk with Method C (reverse pair) polarity
- Use an MTP/MPO Trunk with Method A (straight through polarity), a straight through fiber jumper at one end and a standard A-B, B-A jumper at the other end.

Features & Benefits

Housed in a rugged steel enclosure guaranteed for life

Specifications

General Info

Product Line	C2G	Color	Brown
UPC Number	757120391258	Country Of Origin	United States
Application Sector	Commercial, Industrial	Type	Cassette, Modules

Technical Information

Fiber Optic Cable Type	MPO, MTP, Multimode	Number of Ports	12
Connector 2	ST Female	Connector 1	MTP Female