

Small form factor: 1.125in x 5.125in x 4.5in. This breakout module provides the mechanical distribution of two 12-strand MTP/MPO connectors. Housed in a rugged steel enclosure guaranteed for life, this durable module arrives fully loaded with the preterminated and tested MTP/MPO breakout harness. It is shipped with a test report that can assist in calculating the optical budget.



Not only does that reduce your installation time, but it also ensures optimum quality, performance and consistency. For additional flexibility, you can this in one of our rack or wallmount enclosures which feature scalable designs that can grow with your network system.

Please Note: Custom module configurations supporting other fiber types are also available upon request, and can be quickly fulfilled.

Note: This cassette uses Method A(straight through polarity). To ensure proper transmit to receive polarity between equipment, use one of the following methods.

- Use an MTP/MPO Trunk with Method C (reverse pair) polarity
- Use an MTP/MPO Trunk with Method A (straight through polarity), a straight through fiber jumper at one end and a standard A-B, B-A jumper at the other end.

## Features & Benefits

Small form factor                      Designed for use with two 12-strand 9/125 MTP/MPO cables

## Specifications

### General Info

Product Line	C2G	Color	Blue
UPC Number	757120391401	Country Of Origin	United States
Application Sector	Commercial, Industrial	Type	Cassette, Modules

### Technical Information

Fiber Optic Cable Type	MPO, MTP, Single-Mode	Number of Ports	24
Connector 2	LC Female	Connector 1	MTP Female