



C2G
Discontinued - 1.5ft (0.46m) Pro-Audio XLR Male to 1/4in Male Cable
Part No. CG-40033



Use this XLR to 1/4in cable to connect unbalanced sources to balanced XLR inputs. This pro-audio cable is made from 22 AWG twisted pair audio cable under an aluminum foil shield and 60% copper braid for maximum shielding from noise. The highly flexible 7mm PVC jacket reduces the risk of the cable kinking and damaging the conductors.

Bright nickel plating on solid brass connectors resists wear from reconfiguring and moving equipment from one venue to another. Spring strain relief on the 1/4in plug and a chuck strain relief inside the XLR reduce the effects of age on the solder joints and contacts.

Features & Benefits

Designed to connect unbalanced sources to balanced XLR inputs

Aluminum foil shield and 60% copper braid for maximum shielding from noise

Spring strain relief on the plug and a chuck strain relief inside the XLR

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120400332	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Cable Length	1.5 ft
--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Cable Type	Adapter, Audio
Jacket Rating	Standard / Non-Rated	Connector 2	1/4in TS Male
Connector 1	XLR 3-pin Male		