



Use this Tip/Ring/Sleeve (TRS) configuration cable to connect balanced line outputs to balanced line inputs. This pro-audio cable is made from 22 AWG twisted pair audio cable under an aluminum foil shield and 60% copper braid for maximum shielding from noise. The highly flexible 7mm PVC jacket reduces the risk of the cable kinking and damaging the conductors.

Bright nickel plating on solid brass connectors resists wear from reconfiguring and moving equipment from one venue to another. Spring strain relief on the 1/4in plug reduces the effects of age on the solder joints and contacts.

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------------------|-------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120400714 | Country Of Origin | China |
| Application Sector | Commercial, Residential | Type | Cable |

Dimensions

| | |
|--------------|--------|
| Cable Length | 1.5 ft |
|--------------|--------|

Technical Information

| | | | |
|-----------------|--------------------------|---------------|----------------------|
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 22 AWG |
| Cable Type | Adapter, Audio | Jacket Rating | Standard / Non-Rated |
| Connector 2 | 1/4in TRS Male | Connector 1 | 1/4in TRS Male |