



Performing at the very highest level, the SonicWave interconnect is meticulously crafted to ensure full, accurate and interference-free delivery of critical video signals. Silver-plated oxygen-free copper (OFC) twisted-pair conductors and a nitrogen-foamed PE dielectric are purposely designed to deliver delicate video signals with perfect fidelity regardless of the cable length! The precision 75 Ohm video coaxial cable passes video signals with ultimate stability.

Our Cu Shielding Technology™ provides three layers of shielding: two 80%+ OFC copper braids and one 100% overlapped foil. This extensive shielding ensures immunity to environmentally induced noise, and guarantees the full resolution of the video signal is delivered to the downstream component. SplitLok™ corrosion-resistant, 24K gold-plated connectors feature the use of precision-machined surfaces and a split centerpin for a solid, dependable electrical contact.

Precise soldering techniques using expensive silver solder create increased electrical integrity, maximum signal transfer, long term reliability, and guarantee performance under the most demanding conditions. The Flexcable™ ultra-flexible PVC jacket enables easy installation, and resists binding and kinking which can cause errors in the signal path.

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------|-------|
| Product Line | C2G | Color | Gray |
| Application Sector | Commercial, Residential | Type | Cable |

Dimensions

| | |
|--------------|--------|
| Cable Length | 1.5 ft |
|--------------|--------|

Technical Information

| | | | |
|---------------------|--------------------------|-------------|--------------------------|
| Signal Transmission | Bidirectional | Cable Type | Video |
| Connector 2 | RCA Composite Video Male | Connector 1 | RCA Composite Video Male |