



Video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.41in total depth) save valuable space in the gang box.

This cable is constructed from three 75 Ohm coaxial cables using 26 AWG center conductors and features a tinned copper braid that provides 92% coverage over a foil shield. This design protects the cable from any EMI/RFI interference and ensures that the highest quality signal is transferred for optimal video performance.

CMG-rated cables meet many NEC requirements for Communications Cables General Purpose In Wall Use. Our cables meet the following ratings: CMG, FT4, CM, CL3, CL2, CMX, CL3X, and CL2X.

Always check with your local authority on building requirements to verify cable requirements before beginning any installation.

Specifications

General Info

| | | | |
|-------------------|-------|--------------------|-------------------------|
| Product Line | C2G | UPC Number | 757120401230 |
| Country Of Origin | China | Application Sector | Commercial, Residential |
| Type | Cable | | |

Dimensions

| | |
|--------------|-------|
| Cable Length | 50 ft |
|--------------|-------|

Technical Information

| | | | |
|--------------------|--------------------------|---------------------|--------------------------|
| Jacket Application | In-Wall Rated | Signal Transmission | Bidirectional |
| Cable Type | Video | Jacket Rating | CMG Rated, FT4 Rated |
| Connector 2 | RCA Component Video Male | Connector 1 | RCA Component Video Male |