



Ensure optimal performance from your state-of-the-art equipment with our premium HDMI to DVI-D bi-directional cable. Deliver high resolution digital video from an HDMI-equipped device to a DVI-equipped device, or vice versa. This is a high performance home theater interconnect for high-definition DVD players, HDTV receivers, TV sets, projectors, a/v receivers, and other HDMI-equipped devices. Enjoy ultra-high resolution digital video delivered through a high performance connection.

Advanced cable design, top quality materials, and superior construction maximize the experience and leave nothing to chance. Performance-enhancing features include silver-coated oxygen-free copper (OFC) conductors with nitrogen-injected dielectric, 24-karat gold-plated connectors with silver solder construction, and durable, protective metal connector shells. Two 80%+ OFC braids and 100% overlapped foil combine for full shielding against EMI/RFI interference. This fully-functional, high-bandwidth cable is designed to perform beyond industry standards, and each cable undergoes a final visual test prior to shipment.

Please Note: HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

Features & Benefits

Bi-directional adapter cable, HDMI to DVI or DVI to HDMI

Supports up to a 1080p resolution

In-wall, CL2-rated jacket

Durable, protective metal connector housing

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120402916	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Adapter, Cable

Dimensions

Product Length US	23.0 FT	Cable Length	23 ft
Outside Diameter	7.3 mm		

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Video Resolution	1080p	Jacket Application	In-Wall Rated
Bend Radius	50 mm	Shielded/Unshielded	Shielded
Cable Type	Adapter, Video	Jacket Rating	CL2 Rated, FT4 Rated
Temperature Rating	80° C	Cable Diameter	7.3 mm
Data Transfer Rate	10.2 Gbps	Connector 2	DVI-D Single Link Male

Connector 1	HDMI Male	Video Output Support	DVI-D, HDMI
Operating Temperature	-20°-80°C	Video Input Support	DVI-D, HDMI