



Your expensive HDTV video projector deserves a SonicWave BNC breakout cable. This breakout cable ensures state-of-the-art performance through advanced cable design, construction and materials. Silver-plated oxygen-free copper center conductors and nitrogen-foamed PE dielectric combine with Cu Shielding Technology™ and 24K gold-plated connectors to provide a lifetime of dependable performance.

Three layers of shielding, two 80%+ OFC braids and 100% overlapped foil, provide maximum immunity to environmental EMI/RFI interference. Precise construction techniques maintain characteristic 75 Ohm impedance to guarantee maximum signal fidelity. Silver solder is used to eliminate the negative effects of dissimilar metals, and create increased electrical integrity with maximum transfer of the delicate video signal. The Flexcable™ ultra-flexible PVC jacket enables easy installation.

Features & Benefits

Supports RGBHV video

75 ohms conductor construction

Braided and foil shield to protect from interference

Specifications

General Info

Product Line	C2G	Color	Gray
--------------	-----	-------	------

Type	Cable
------	-------

Dimensions

Cable Length	3 ft
--------------	------

Technical Information

Cable Type	Adapter, Breakout, Video	Adapter Rear	BNC RGBHV Male
------------	--------------------------	--------------	----------------

Adapter Front	VGA Male
---------------	----------