



Audio/video installations in educational and commercial settings often require plenum-rated cabling. Our plenum-rated line was engineered to overcome common challenges faced by installers. Low-profile connectors (1.5in total depth) save valuable space and enable easier in-wall connections. And our small-diameter (0.25in) cable design further reduces the space and clearance required to run the necessary cabling through walls and plenum air spaces.

This cable is constructed from three 75 Ohm coaxial cables using 26 AWG center conductors and featuring a tinned copper braid that provides 92% over foil shield. CMP rating provides the fire protection required to run within walls and air plenums without the need for conduit.

Features & Benefits

Supports a Stereo Audio signal	Plenum, CMP-rated jacket
24 AWG conductor construction	Low profile connectors

Specifications

General Info

Product Line	C2G	UPC Number	757120405221
Country Of Origin	China	Application Sector	Commercial, Residential
Type	Cable		

Dimensions

Cable Length	75 ft	Outside Diameter	3.4 mm
--------------	-------	------------------	--------

Technical Information

Wire Gauge	22 AWG	Jacket Application	Plenum Rated
Cable Type	Audio	Jacket Rating	CMP Rated, FT6 Rated
Temperature Rating	75° C	Cable Diameter	3.4 mm
Connector 2	3.5mm Stereo Male	Connector 1	3.5mm Stereo Male