



C2G
50ft (15.2m) Composite Video and Stereo Audio Cable with Low Profile Connectors M/M - Plenum CMP-Rated
Part No. CG-40526

Audio/video installations in educational and commercial settings often require plenum-rated cabling. Our plenum-rated line was engineered to overcome common challenges faced by installers. Low-profile connectors (1.5in total depth) save valuable space and enable easier in-wall connections. And our small-diameter (0.25in) cable design further reduces the space and clearance required to run the necessary cabling through walls and plenum air spaces.



This cable is constructed from three 75 Ohm coaxial cables using 26 AWG center conductors and featuring a tinned copper braid that provides 92% over foil shield. CMP rating provides the fire protection required to run within walls and air plenums without the need for conduit.

Features & Benefits

Supports Composite Video and RCA Stereo Audio	Plenum, CMP-rated jacket
Low profile connectors	26 AWG conductor construction

Specifications

General Info

Product Line	C2G	UPC Number	757120405269
Country Of Origin	China	Type	Cable

Dimensions

Cable Length	50 ft
--------------	-------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
Cable Type	Audio, Video	Jacket Rating	Plenum CMP-Rated
Adapter Rear	RCA Composite Video Male, RCA Stereo Audio Male	Adapter Front	RCA Composite Video Male, RCA Stereo Audio Male