

The ideal, high performance solution for video presentations, video projectors, plasma screens, LCD or CRT monitors, KVM switches, and in installations where the cable must perform over long distances. One 3.5mm male stereo plug on each cable end connects your audio source. The plenum rating is a necessity for any systems integrator working on an educational or commercial installation.



Cable construction consists of three 75 Ohm 28 AWG coax cables plus three 26 AWG twisted pairs and two 26 AWG conductors ensuring signal integrity in your installation.

The coax cables feature a tinned copper braid providing 93% shield. Besides the metal HD15 connector housing, the cable is shielded by a tinned copper braid providing a minimum of 85% coverage, and by aluminum foil and drain wire to provide 100% coverage.

The low-smoke CMP-rated PVC outer jacket provide the fire protection required to run these cables within walls and air plenums without the need for conduit. Don't be misled by cable dealers selling low cost, so-called plenum cables that Don't meet the minimum requirements for plenum rating, those cables will cost you much more in the end. Instead, trust our plenum-rated high resolution cable for your installation!

UXGA provides a screen resolution of 1600 x 1200 pixels.

Please Note: Pin 9 is not loaded. Pin 9 is not required for standard computer video applications.

Features & Benefits

Supports up to a 1600x1200 resolution

Plenum, CMP-rated jacket

Shielded to help reduce interference

Durable metal connectors

Specifications

General Info

Product Line	C2G	UPC Number	751120406846
Country Of Origin	China	Application Sector	Residential, Commercial
Type	Cable		

Dimensions

Cable Length	50 ft
--------------	-------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Cable Type	Video	Jacket Rating	Plenum CMP-Rated
Adapter Rear	VGA Male, 3.5mm Stereo Male	Adapter Front	VGA Male, 3.5mm Stereo Male
