



Our s-video cable is constructed from high quality multiple conductors that deliver high quality video images. Separate conductors carry the Y-component (Chrominance) separately from the C-component (Luminance), to provide higher resolution and better picture quality than a composite video cable. Molded connectors with integrated strain relief; flexible PVC jacket.

## Features & Benefits

Supports a S-Video signal

Fully molded connector and strain relief

Flexible PVC jacket

## Specifications

### General Info

|                   |       |                    |                         |
|-------------------|-------|--------------------|-------------------------|
| Product Line      | C2G   | UPC Number         | 757120409205            |
| Country Of Origin | China | Application Sector | Residential, Commercial |
| Type              | Cable |                    |                         |

### Dimensions

|              |        |
|--------------|--------|
| Cable Length | 100 ft |
|--------------|--------|

### Additional Information

|                          |     |                          |                              |
|--------------------------|-----|--------------------------|------------------------------|
| Prop 65 Warning Required | Yes | Prop 65 Warning Language | Cancer and Reproductive Harm |
|--------------------------|-----|--------------------------|------------------------------|

### Technical Information

|            |       |              |              |
|------------|-------|--------------|--------------|
| Cable Type | Video | Adapter Rear | S-Video Male |
|------------|-------|--------------|--------------|

---

Adapter Front

S-Video Male

---