



C2G
50ft (15.2m) Pro Series Single Link DVI-D™ Digital Video Cable M/M - Plenum CMP-Rated
Part No. CG-41203

Strict building code requirements for cabling in plenum spaces have created installation challenges in settings such as schools, hospitals and other commercial buildings. Previous solutions were limited to "over Cat5/6" products, which added to both the complexity and the reliability of the installation due to the need for power and signal conversion. C2G, formerly Cables To Go, has expanded its connectivity portfolio to include a line of commercial grade plenum cables that are ideal for routing audio/video cables through plenum space above dropped ceilings or under raised floors.

The new Pro Series commercial grade plenum cables offer true digital performance while meeting the highest standards in fire resistance. Available for HDMI®, DVI and DVI+3.5mm audio signals, these cables can meet the demands of virtually any commercial installation.

By supporting resolutions of 1080p for displays and up to 1920 x 1200 pixels for computers, and with lengths ranging from 6 to 50 feet, the Pro Series is the ideal connectivity solution for A/V equipment used in classrooms or conference rooms. 24k gold-plated connectors prevent metal corrosion, resulting in the optimal signal transfer for the highest picture and sound quality. Shielded 24AWG copper conductors protect against EMI and RFI to ensure uninterrupted performance. High quality materials and construction, along with rigorous factory testing and a full lifetime warranty, guarantee long-term, dependable performance.

*CL2 is equivalent to FT4 rating in Canada, while CMP is equivalent to FT6.

Please Note: Does not support analog video; only supports digital video signal.



Features & Benefits

Plenum, CMP-rated	Supports up to a 1920x1200 resolution
Gold plated connectors	24 AWG conductor construction

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120412038	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	50.0 FT	Cable Length	50 ft
Outside Diameter	8.35 mm		

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
-----------------	--------------------------	------------	--------

Video Resolution	WUXGA (1920x1200)	Jacket Application	Plenum Rated
Shielded/Unshielded	Shielded	Cable Type	Video
Jacket Rating	CMP Rated, FT6 Rated	Cable Diameter	8.35 mm
Connector 2	DVI-D Single Link Male	Connector 1	DVI-D Single Link Male
Video Output Support	DVI-D	Video Input Support	DVI-D
