



Send video signal from an existing desktop computer or another source device with a DVI-D video output port to a projector or monitor with a DisplayPort input. This converter is an ideal solution schools, conference rooms, or other work spaces when upgrading to a new monitor or projector.

Straightforward install

There is no need for an external graphics adapter or extra converters. This simple plug and play converter changes the DVI-D output signal to DisplayPort, no drivers are required for install nor additional power adapters. The all in one dongle style converter provides power from an onboard USB connection and requires no drivers for install.

Supports cost savings

Newer displays no longer offer DVI-D as an input. Utilizing this DVI to DisplayPort converter will allow for connection to a brand new monitor or projector without the added expense of updating the graphics card.

Port protection technology

The dongle style adapter reduces strain on the video port. The cable between the DVI-D connection and the converter provide strain relief that protects the port from strain damage as cords are moved.

Simple power

No need to utilize a power adapter. The DVI to DisplayPort converter pulls power from the DVI-D port bus power. If enough power is not supplied by the DVI port there is a USB plug attached to the converter which provides power as well.

Features & Benefits

Allows connection of desktop computer or source device with DVI-D output to a monitor or projector with DisplayPort input	Easy and straightforward installation process
Saves cost by avoiding the need to update graphics card	Protects video port from strain damage
No need for external power adapter	Provides flexibility with additional power option through USB plug

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120413790	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Active Device, Adapter, Converter

Dimensions

Product Width US	1.34 in	Product Height US	0.65 in
Product Length US	2.65 in		

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	34 AWG
Video Resolution	1080p	Bend Radius	12 mm
Jacket Rating	Standard / Non-Rated	Cable Diameter	4.8 mm
Connector 2	DisplayPort Female	Connector 1	DVI-D Dual Link Male, USB-A Male
Video Output Support	DisplayPort	Operating Temperature	0°-70°C
Video Input Support	DVI-D	Voltage	30.0 V
Storage Temperature	-10° - 40° C		