



The Ultima USB cable optimizes style, quality, and value in a cable specially designed for high performance. keyboards, mice, modems, printers, and other USB peripherals, and this cable will deliver high speed data transfer up to 480 Mbps. heavy duty 24 AWG power wires provide the proper current to your USB device. Dual foil and braid shielding reduces EMI/RFI interference while twisted pair construction helps reduce crosstalk thus ensuring high speed, error-free data transfer.

The sleek design of the molded connectors makes them easy to grip. The metal connector shield helps to meet FCC requirements on EMI/RFI interference, while a solder-to-connector shell and cable braid create an end-to-end shielding solution for a noise-free connection.

24k gold-plated connectors provide maximum corrosion resistance for error-free data transfer. The charcoal gray cable jacket not only matches your case but disappears behind your desk leaving a clean organized look. Finally, an ultra-flexible jacket makes installation easy.

Features & Benefits

Foil and braid shielding reduces interference for error-free data transfer

Molded strain relief ensures durability and longevity

Ample length provides flexibility in device placement

High-speed data transfer ensures efficient and reliable performance

Shielding reduces interference, ensuring error-free data transfer

Molded strain relief ensures durability and longevity, even with frequent use

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120450030	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	9.8 FT	Cable Length	9.8 ft
-------------------	--------	--------------	--------

Outside Diameter 4.7 mm

Technical Information

Jacket Material PVC (Polyvinyl Chloride) Wire Gauge 24 AWG

Storage Humidity 20-80% RH (Non-Condensing) Bend Radius 47 mm

Conductor Stranding Stranded Signal Transmission Bidirectional

Cable Type USB Data Transfer Rate 480 Mbps

Connector 2 USB-B Male Connector 1 USB-A Male

Operating Temperature -20°-80°C Operating Humidity 20-80% RH (Non-Condensing)

Storage Temperature -20° - 80° C
