



**C2G**  
**3ft (0.9m) Select VGA Video Cable M/M - In-Wall CMG-Rated**  
Part No. CG-50211



The C2G Select VGA Video Cable is perfect for source to display connectivity for in-home desktop or in-wall commercial applications which require video resolutions of up to QXGA (2048x1536). The CMG rated jacket provides a solution for in-wall applications, while the low-profile, rounded connectors make installing in tight spaces, such as a projector mount pole, easy. This cable is designed to support high resolution video applications over long distances of up to 150ft. All 15 pins are wired providing support for DDC2 (E-DDC) and Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, ensuring that the content from the source is sent at the optimal resolution for the display.

<

## Features & Benefits

In-wall, CMG-rated jacket

Supports up to a 2048x1536 resolution

All 15 pins wired to support DDC2 (E-DDC) and EDID

Low profile connectors

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120502111	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
Outside Diameter	8.5 mm		

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	QXGA (2048x1536)	Jacket Application	In-Wall Rated

---

Bend Radius	51 mm	Cable Type	Video
Jacket Rating	CMG Rated, FT4 Rated	Cable Diameter	8.5 mm
Connector 2	VGA Male	Connector 1	VGA Male
Video Output Support	VGA	Video Input Support	VGA
Voltage	30.0 V		

---