



C2G

**Discontinued - 125ft (38.1m) Select VGA + 3.5mm Stereo Audio A/V Cable M/M - In-Wall CMG-Rated**  
Part No. CG-50233



The C2G Select VGA + 3.5mm A/V Cable is perfect for source to display connectivity for in-home desktop or in-wall commercial applications which require video resolutions of up to QXGA (2048x1536) and support for stereo audio. The CMG rated jacket provides a solution for in-wall applications, while the low-profile, rounded connectors make installing in tight spaces, such as a projector mount pole, easy. This cable is designed to support high resolution video applications over long distances of up to 150ft. The 3.5mm audio pigtail on the source side of the cable extends 24 inches away from the VGA connector. This allows for audio connectivity on laptops or other computer platforms where the VGA video output and 3.5mm audio output are commonly placed on opposite sides. The 3.5mm audio pigtail on the display side of the cable extends 10 inches away from the VGA connector providing easy connectivity without excess cabling. All 15 pins are wired providing support for DDC2 (E-DDC) and Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, ensuring that the content from the source is sent at the optimal resolution for the display.

<

## Features & Benefits

In-wall, CMG-rated jacket

Supports up to a 2048x1536 resolution

All 15 pins wired to support DDC2 (E-DDC) and EDID

Low profile connectors

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120502333	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

### Dimensions

Cable Length	125 ft	Outside Diameter	9 mm
--------------	--------	------------------	------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Video Resolution	QXGA (2048x1536)	Jacket Application	In-Wall Rated
Bend Radius	85 mm	Cable Type	Audio, Video
Jacket Rating	CMG Rated, FT4 Rated	Cable Diameter	9 mm
Data Transfer Rate	5.4 Gbps	Connector 2	VGA Male, 3.5mm Stereo Male
Connector 1	3.5mm Stereo Male, VGA Male	Video Output Support	VGA
Video Input Support	VGA	Voltage	30.0 V