RapidRun® is designed to be the standard for in-wall audio/video installations. The RapidRun system empowers you to customize your installation to create your own ideal audio/video solution. Break-away flying leads and wall plates ensure flexible, efficient, high quality connections for all types of equipment.

Use this plenum-rated PC Runner for in-wall installations that support computer-based applications. Whether hanging a projector in a modern 21st century classroom or installing a commercial digital signage system, a clean, crisp signal will be delivered every time.

Terminate with flying leads (with lengths up to 10 feet), or with wall plates (available in three colors) to meet the specific requirements of your installation.

Please Note: Each complete RapidRun PC Runner solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. For each runner you will need (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

Features & Benefits

Plenum, CMP-rated jacket

Supports VGA video and other audio/video signals

Designed for use with RapidRun PC flying leads and wall plates

Specifications

General Info

Product Line	C2G	UPC Number	757120507307
Country Of Origin	China	Application Sector	Commercial, Residential
Warranty Type	Lifetime	Type	Cable

Dimensions

Cable Length	35 ft

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Jacket Application	Plenum Rated
Bend Radius	82.5 mm	Cable Type	Runner

Jacket Rating	CMP Rated, FT6 Rated	Cable Diameter	7 mm
Adapter Rear	RapidRun 15-pin Female	Adapter Front	RapidRun 15-pin Female