

Audio/Video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.25 in total depth) save valuable space in the gang box, while the rounded shape accommodates smaller monitor mounts so that the cable can be easily hidden from view.



Specifically designed to support RS-232/Serial communications, this cable is fully shielded to prevent unwanted EMI/RFI interference. The fully molded cable design delivers excellent strain relief, while connector thumbscrews provide a quick and easy connection every time.

The transmit and receive signals are crossed to ensure proper data transmission.

CMG-rated cables meet with many NEC requirements for Communications Cables - General Purpose In Wall Use. Our cables meet the following ratings:

[\*] CMG, FT4 (Canada)

## Features & Benefits

- In-wall, CL2-rated jacket
- Low profile connectors
- Null modem wiring scheme

## Specifications

### General Info

Product Line	C2G	UPC Number	757120521822
Country Of Origin	Vietnam	Application Sector	Residential, Commercial, Industrial
Type	Cable		

### Dimensions

Cable Length	75 ft
--------------	-------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG
Cable Type	Serial, Null Modem	Jacket Rating	CMG (FT4) Rated
Adapter Rear	DB9 Female	Adapter Front	DB9 Female