

C2G Mini DisplayPort™ to HDMI® Active Adapter Converter 4K 30Hz - White

This adapter allows the Mini DisplayPort™ video output of a laptop to connect to the HDMI® input of a display and is perfect for applications including displaying video on an HDTV, projector, or monitor in a classroom, on a desktop, or in a meeting room. This Mini DisplayPort to HDMI active adapter can be used in either DisplayPort single-mode or dual-mode outputs, providing the conversion for a Mini DisplayPort source even when that source does not support DP++. Active Mini DisplayPort conversion is excellent for applications where multiple Mini DisplayPort adapters are required to connect to a single graphics card. This allows every active adapter to interface with a corresponding display. This adapter is a perfect accessory for Microsoft® Surface® products and other leading laptops.

On The Go Enhanced

Part No. CG-54308

Be prepared for any meeting, presentation, or event with the full confidence that you have the right connection in an ultra-compact design. The Mini DisplayPort to HDMI adapter can connect a Mini DisplayPort equipped laptop or tablet to a projector, monitor, or HDTV with a HDMI input port. The compact design of this adapter converter makes it a perfect fit for BYOD (Bring Your Own Device) applications in education or corporate environments.

Straightforward Install

This simple plug and play adapter converter does not require drivers for install and the device is powered through Mini DisplayPort bus power, so no additional power adapters are needed.

Port Protection

The dongle-style adapter converter reduces strain on the video port. The cable between the Mini DisplayPort connection and the adapter converter provides strain relief that protects the port from strain damage as cords are moved.

Note: When this device is connected to a Mini DisplayPort source device that supports audio and an DVI-D to HDMI Cable with the HDMI connector plugged into a HDMI display device that supports audio both audio and video signal will be transmitted from the source device to the display device. However connecting to a DVI-D display will not allow audio to pass to the display.

Discover more connectivity solutions for the Microsoft Surface



Features & Benefits

Active Conversion of Mini DisplayPort to HDMI

Supports resolutions up to 4K (4096 x 2160 at 30Hz)

Dongle style adapter reduces strain on ports

Compatible with the Microsoft® Surface® Pro 6, Surface Laptop 2, and other leading laptops

Specifications

General Info

Product Line	C2G	Color	White
UPC Number	757120543084	Country Of Origin	China
Application Sector	Commercial, Residential	Туре	Active Device, Adapter, Converter
Dimensions			
Product Width US	1.77 in	Product Height US	0.59 in
Product Length US	1.77 in	Cable Length	0.67 ft
Listing Agencies / 3rd	l Party Agencies		
CE Certified	Yes	FCC Compliant	Yes
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	32 AWG
Video Resolution	1080p, 4K, 4K 30Hz	Bend Radius	51 mm
Number of Ports	1	Jacket Rating	Standard / Non-Rated
Cable Diameter	5.2 mm	Data Transfer Rate	18 Gbps
Connector 2	HDMI Female	Connector 1	Mini DisplayPort Male
Video Output Support	HDMI	Operating Temperature	0°-50°C
Video Input Support	Mini DisplayPort	Voltage	30.0 V
Storage Temperature	-25° - 70° C		