

This adapter cable is an ideal solution for connecting the Mini DisplayPort or Thunderbolt 2 output of a small laptop or tablet to a computer monitor which accepts a DVI-D input. This cable carries a digital video signal, supports up to a 1920x1200 resolution and meets the requirements of high performance applications. This adapter cable is a perfect accessory for Microsoft® Surface® products and other leading laptops.



Discover more connectivity solutions for the [Microsoft Surface](#)

## Features & Benefits

Directly connect a Mini DisplayPort/Thunderbolt 2 output to a Single Link DVI-D input

Carries a digital video signal

Supports up to a 1920x1200 resolution

Compatible with the Microsoft® Surface® Pro 6, Surface Laptop 2, and other leading laptops

## Specifications

### General Info

|                    |                               |                   |        |
|--------------------|-------------------------------|-------------------|--------|
| Product Line       | C2G                           | Color             | Black  |
| UPC Number         | 757120543367                  | Country Of Origin | China  |
| Application Sector | Commercial, Residential       | Warranty Type     | 5-Year |
| Type               | Active Device, Adapter, Cable |                   |        |

### Dimensions

|                   |         |              |       |
|-------------------|---------|--------------|-------|
| Product Length US | 10.0 FT | Cable Length | 10 ft |
| Outside Diameter  | 5.2 mm  |              |       |

### Listing Agencies / 3rd Party Agencies

|              |     |               |     |
|--------------|-----|---------------|-----|
| CE Certified | Yes | FCC Compliant | Yes |
|--------------|-----|---------------|-----|

### Technical Information

---

|                       |                          |                      |                        |
|-----------------------|--------------------------|----------------------|------------------------|
| Jacket Material       | PVC (Polyvinyl Chloride) | Wire Gauge           | 32 AWG                 |
| Video Resolution      | 1080p, WUXGA (1920x1200) | Shielded/Unshielded  | Shielded               |
| Cable Type            | Adapter, Video           | Jacket Rating        | Standard / Non-Rated   |
| Cable Diameter        | 5.2 mm                   | Connector 2          | DVI-D Single Link Male |
| Connector 1           | Mini DisplayPort Male    | Video Output Support | DVI-D                  |
| Operating Temperature | 0°-50°C                  | Video Input Support  | Mini DisplayPort       |
| Voltage               | 30.0 V                   | Storage Temperature  | -25° - 70° C           |

---