

The Mini DisplayPort to HDMI Passive Adapter Converter is an ideal solution for streaming high-quality audio/video content from the Mini DisplayPort or Thunderbolt 2 output of a laptop to an HDTV or projector which accepts an HDMI input # making it a perfect solution for the office, work space applications, or conference rooms.



This passive adapter converter is a simple plug and play solution that has a DisplayPort 1.2a input and an HDMI 1.4b output. It supports high-definition resolutions up to 4K (3840 x 2160 at 30Hz) and is powered from the Mini DisplayPort source device # allowing it to deliver high quality audio and video to the connected display.

Note:

If the source device supports dual-mode DisplayPort (also known as DP++), a passive adapter can be used because the source device can perform the conversion. If the source device does not support DP++, then an active adapter converter should be used. Thunderbolt 2 ports support DP++ natively.

Features & Benefits

Adapts a Mini DisplayPort/Thunderbolt 2 output to HDMI	Supports DisplayPort 1.2a input and HDMI 1.4b output
Supports resolutions up to 4K (3840 x 2160 at 30hz)	Powered from DisplayPort source

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120544302	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter, Converter		

Dimensions

Product Length US	0.67 FT	Cable Length	0.67 ft
-------------------	---------	--------------	---------

Listing Agencies / 3rd Party Agencies

FCC Compliant	Yes
---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Operating Temperature Min	0 °C
Video Resolution	1080p, 4K, 4K 30Hz	Storage Humidity	5-90% RH (Non-Condensing)

Number of Ports	1	Operating Temperature Max	45 °C
Jacket Rating	Standard / Non-Rated	Data Transfer Rate	2.7 Gbps
Connector 2	HDMI Female	Connector 1	Mini DisplayPort Male
Video Output Support	HDMI	Operating Temperature	0°-45°C
Operating Humidity	10-85% RH (Non-Condensing)	Video Input Support	Mini DisplayPort
Storage Temperature	-10° - 80° C		
