



**C2G**  
**10ft (3m) DisplayPort™ Male to HDMI™ Male Passive Adapter Cable - 4K 30Hz**  
Part No. CG-54434



The DisplayPort to HDMI Passive Adapter Cable is an ideal solution for streaming high-quality audio/video content from the DisplayPort output of a laptop to an HDTV or projector which accepts an HDMI input # making it a perfect solution for the office, work space applications, or conference rooms.

The cable form factor of this adapter provides a simple and convenient solution that eliminates the need for a separate adapter and cable, reducing possible failure points.

This passive adapter cable is a simple plug and play solution that has a DisplayPort 1.2a input and an HDMI 1.4b output. It supports high-definition resolutions up to 4K (3840 x 2160 at 30Hz) and is powered from the DisplayPort source device # allowing it to deliver high quality audio and video to the connected display.

**Note:**

If the source device supports dual-mode DisplayPort (also known as DP++), a passive adapter can be used because the source device can perform the conversion. If the source device does not support DP++, then an active adapter converter should be used. Thunderbolt 2 ports support DP++ natively.

## Features & Benefits

Adapts a DisplayPort output to HDMI

Supports DisplayPort 1.2a input and HDMI 1.4b output

Supports resolutions up to 4K (3840 x 2160 at 30hz) Supports up to 192kHz audio frame rate and up to 24-bit audio sample size

Powered from DisplayPort source

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120544340	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter, Cable		

### Dimensions

Product Length US	10.0 FT	Cable Length	10 ft
-------------------	---------	--------------	-------

### Listing Agencies / 3rd Party Agencies

---

FCC Compliant	Yes
---------------	-----

---

### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	1080p, 4K, 4K 30Hz
-----------------	--------------------------	------------------	--------------------

---

Storage Humidity	5-90% RH (Non-Condensing)	Cable Type	Adapter, Video
------------------	---------------------------	------------	----------------

---

Jacket Rating	Standard / Non-Rated	Data Transfer Rate	2.7 Gbps
---------------	----------------------	--------------------	----------

---

Connector 2	HDMI Male	Connector 1	DisplayPort Male
-------------	-----------	-------------	------------------

---

Video Output Support	HDMI	Operating Temperature	0°-45°C
----------------------	------	-----------------------	---------

---

Operating Humidity	10-85% RH (Non-Condensing)	Video Input Support	DisplayPort
--------------------	----------------------------	---------------------	-------------

---

Storage Temperature	-10° - 80° C
---------------------	--------------

---