

RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.



Ideal for educational and institutional installations, this wall plate receives PC video, 3.5mm stereo audio, USB and RCA composite audio/video from one Runner cable. Constructed from aluminum for durability, this wall plate has a locking connector that enables the integrator to save valuable space inside the surface mount or electrical box that typically is already packed with cables. The included keystone bezels will work with most brands of keystone inserts including Leviton®, L-com®, NetKey®, ADC Krone, HellermannTyton, and Allen Tel.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

## Features & Benefits

In-wall, CMG-rated jacket

Supports VGA video and other audio/video signals

Designed for use with RapidRun Multi-Format flying leads and wall plates

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120600008	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

### Dimensions

Product Length US	6.0 FT	Cable Length	6 ft
Outside Diameter	9 mm		

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
-----------------	--------------------------	------------	--------

---

Video Resolution	UXGA (1600x1200)	Jacket Application	In-Wall Rated
Bend Radius	90 mm	Shielded/Unshielded	Shielded
Cable Type	Audio, Runner, Video	Jacket Rating	CMG Rated, FT4 Rated
Temperature Rating	80° C	Cable Diameter	9 mm
Connector 2	RapidRun 15-pin Female	Connector 1	RapidRun 15-pin Female
Video Output Support	VGA	Video Input Support	VGA

---