

RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.



Ideal for educational and institutional installations, this wall plate receives PC video, 3.5mm stereo audio, USB and RCA composite audio/video from one Runner cable. Constructed from aluminum for durability, this wall plate has a locking connector that enables the integrator to save valuable space inside the surface mount or electrical box that typically is already packed with cables. The included keystone bezels will work with most brands of keystone inserts including Leviton®, L-com®, NetKey®, ADC Krone, HellermannTyton, and Allen Tel.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

## Features & Benefits

In-wall, CMG-rated jacket

Supports VGA video and other audio/video signals

Designed for use with RapidRun Multi-Format flying leads and wall plates

## Specifications

### General Info

|                    |                         |                   |          |
|--------------------|-------------------------|-------------------|----------|
| Product Line       | C2G                     | Color             | Black    |
| UPC Number         | 757120600053            | Country Of Origin | China    |
| Application Sector | Commercial, Residential | Warranty Type     | Lifetime |
| Type               | Cable                   |                   |          |

### Dimensions

|                   |         |              |       |
|-------------------|---------|--------------|-------|
| Product Length US | 50.0 FT | Cable Length | 50 ft |
| Outside Diameter  | 9 mm    |              |       |

### Technical Information

---

|                      |                          |                     |                        |
|----------------------|--------------------------|---------------------|------------------------|
| Jacket Material      | PVC (Polyvinyl Chloride) | Wire Gauge          | 24 AWG                 |
| Video Resolution     | UXGA (1600x1200)         | Jacket Application  | In-Wall Rated          |
| Bend Radius          | 90 mm                    | Shielded/Unshielded | Shielded               |
| Cable Type           | Audio, Runner, Video     | Jacket Rating       | CMG Rated, FT4 Rated   |
| Temperature Rating   | 80° C                    | Cable Diameter      | 9 mm                   |
| Connector 2          | RapidRun 15-pin Female   | Connector 1         | RapidRun 15-pin Female |
| Video Output Support | VGA                      | Video Input Support | VGA                    |

---