



C2G

75ft (22.8m) RapidRun® Multi-Format Runner Cable - Plenum CMP-Rated

Part No. CG-60014

RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Constructed from aluminum for durability, this wall plate has a locking connector that enables the integrator to save valuable space inside the surface mount or electrical box that typically is already packed with cables. The included keystone bezels will work with most brands of keystone inserts including Leviton®, L-com®, NetKey®, ADC Krone, HellermannTyton, and Allen Tel.

For more information on the RapidRun Multi-Format products, click [here](#).

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminat each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.



Features & Benefits

Plenum, CMP-rated jacket

Supports VGA video and other audio/video signals

Designed for use with RapidRun Multi-Format flying leads and wall plates

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120600145	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Product Length US	75.0 FT	Cable Length	75 ft
Outside Diameter	8 mm		

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	26 AWG
-----------------	--------------------------	------------	--------

Video Resolution	UXGA (1600x1200)	Jacket Application	Plenum Rated
Bend Radius	82.5 mm	Shielded/Unshielded	Shielded
Cable Type	Runner	Jacket Rating	CMP Rated, FT6 Rated
Temperature Rating	75° C	Cable Diameter	8 mm
Connector 2	RapidRun 15-pin Female	Connector 1	RapidRun 15-pin Female
Video Output Support	VGA	Video Input Support	VGA
