

RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.



Ideal for educational and institutional installations, this flying lead sends PC video, 3.5mm stereo audio and RCA composite audio/video over one cable. It is commonly used on the display (projector) end of classroom setups with the corresponding wall plate used at the teacher's station.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

<

Features & Benefits

Designed for use with RapidRun Multi-Format runner cables

Compatible with RapidRun Multi-Format VGA, 3.5mm, Composite Video and RCA Stereo Audio wall plates and flying leads

28 AWG and 24AWG conductor construction

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120600190	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Adapter, Cable

Dimensions

Product Length US	3.0 FT	Cable Length	3 ft
Outside Diameter	3.4 mm		

Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Bend Radius	30 mm	Temperature Rating	80° C
Cable Diameter	3.4 mm	Data Transfer Rate	10.2 Gbps

Connector 2	RapidRun 15-pin Male	Connector 1	VGA Male, 3.5mm Stereo Male, RCA Stereo Audio Male, RCA Composite Video Male
Video Output Support	VGA	Operating Temperature	-20°-80°C
Operating Humidity	20-80% RH (Non-Condensing)	Video Input Support	VGA
Storage Temperature	-20° - 80° C		
