



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this wall plate receives PC video, 3.5mm stereo audio and RCA composite audio/video from one Runner cable. Constructed from aluminum for durability, this wall plate has a locking connector that enables the integrator to save valuable space inside the surface mount or electrical box that typically is already packed with cables. The included keystone bezels will work with most brands of keystone inserts including Leviton®, L-com®, NetKey®, ADC Krone, HellermannTyton, and Allen Tel.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

<

## Features & Benefits

Designed for use with RapidRun Multi-Format runner cables      Compatible with RapidRun Multi-Format VGA, 3.5mm, Composite Video and RCA Stereo Audio wall plates and flying leads

## Specifications

### General Info

Product Line	C2G	Color	Ivory
UPC Number	757120600237	Country Of Origin	China
Application Sector	Residential, Commercial	Type	Wall Plate Insert

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Number of Gangs	1	Data Transfer Rate	10.2 Gbps
Adapter Rear	RapidRun 15-pin Male	Adapter Front	VGA Female, 3.5mm Stereo Female, RCA Composite Video Female, RCA Stereo Audio Female