



C2G
1.5ft (0.46m) RapidRun® VGA (HD15) + 3.5mm Flying Lead
Part No. CG-60048



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Use this Plenum-rated Multi-Format Runner for in-wall installations that support high density, multi-format applications. Whether hanging a projector in a modern 21st century classroom or installing a commercial digital signage system, a clean, crisp signal will be delivered every time.

Please note: Each complete RapidRun Multi-Format runner solution requires a break-away flying lead or wall plate to terminat each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

<

Features & Benefits

Designed for use with RapidRun Multi-Format runner cables

Compatible with RapidRun Multi-Format VGA and 3.5mm wall plates and flying leads

28 AWG and 24AWG conductor construction

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120600480	Country Of Origin	Vietnam
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Adapter, Cable		

Dimensions

Product Length US	1.5 FT	Cable Length	1.5 ft
-------------------	--------	--------------	--------

Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Storage Humidity	20-80% RH (Non-Condensing)	Shielded/Unshielded	Shielded

Cable Type	Flying Lead, Video	Jacket Rating	Standard / Non-Rated
Data Transfer Rate	10.2 Gbps	Connector 2	RapidRun 15-pin Male
Connector 1	3.5mm Stereo Male, VGA Male	Video Output Support	VGA
Operating Temperature	-20°-80°C	Video Input Support	VGA
Storage Temperature	-20° - 80° C		