



C2G

**50ft (15.2m) RapidRun® Multi-Format All-In-One Runner Cable - In-Wall CMG-Rated**

Part No. CG-60071



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this flying lead sends PC video and 3.5mm stereo audio over one cable. It is commonly used on the display (projector) end of classroom setups with the corresponding wall plate used at the teacher's station.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminat each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

## Features & Benefits

In-wall, CMG-rated jacket

Integrated VGA, 3.5mm, Composite Video and RCA Stereo Audio connectors

Designed for use with RapidRun Multi-Format flying leads and wall plates

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120600718	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

### Dimensions

Product Length US	50.0 FT	Cable Length	50 ft
Outside Diameter	9 mm		

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG
Video Resolution	UXGA (1600x1200)	Storage Humidity	20-80% RH (Non-Condensing)

Jacket Application	In-Wall Rated	Bend Radius	90 mm
Shielded/Unshielded	Shielded	Cable Type	Audio, Runner, Video
Jacket Rating	CMG Rated, FT4 Rated	Cable Diameter	9 mm
Connector 2	RapidRun 15-pin Female	Connector 1	3.5mm Stereo Male, VGA Male, RCA Stereo Audio Male, RCA Composite Video Male
Video Output Support	VGA	Operating Temperature	-20°-80°C
Video Input Support	VGA	Storage Temperature	-20° - 80° C