RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Use this CMP-rated Multi-Format Runner for in-wall installations that support high density, multi-format applications. Whether hanging a projector in a modern 21st century classroom or installing a commercial digital signage system, a clean, crisp signal will be delivered every time.

For more information on the RapidRun Multi-Format products, click here.

Please note: Each complete RapidRun Multi-Format All-In-One runner solution requires a break-away flying lead or wall plate to terminat with HD15, 3.5mm and 3RCA connections.

Features & Benefits

Supports flexible, high density, multi-format applications

CMP-rated for in-wall installations

Requires a break-away flying lead or wall plate

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120600756	Country Of Origin	China
Application Sector	Commercial, Residential	Type	Cable

Dimensions

Cable Length	6 ft	Outside Diameter	9 mm

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	UXGA (1600x1200)
Jacket Application	In-Wall Rated	Bend Radius	90 mm
Cable Type	Extension, Runner	Jacket Rating	CMG Rated, FT4 Rated
Cable Diameter	9 mm	Connector 2	RapidRun 15-pin Female
Connector 1	RapidRun 15-pin Male		